



## MATERIAL SAFETY DATA SHEET

PRODUCT

**FUEL RIGHT<sup>®</sup> 6000**  
(Bulk Fuel Additive)

Last Revised 1/17/2008

*Emergency Telephone Number:* CHEMTREC (800) 424-9300

### SECTION 1 PRODUCT IDENTIFICATION

TRADE NAME: Fuel Right<sup>®</sup> 6000 Bulk Fuel Additive

DESCRIPTION: A hydrocarbon solution of cyclic and aliphatic amino compounds and a glycol ether.

NFPA 704M/HMIS RATING: 2/2 HEALTH 2/2 FLAMMABILITY 0/0 REACTIVITY 0 OTHER  
0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme

Our hazard evaluation has identified the following chemical ingredients as hazardous. One or more is being claimed as a trade secret under OSHA's Hazard Communication Rule, 29 CFR 1910.1200. Consult Section 14 for the nature of the hazard(s).

### SECTION 2 HAZARDOUS INGREDIENTS

INGREDIENTS	CAS #	APPROX. %
heavy aromatic naphtha	64742-94-5	45-60
a cyclic amino compound	trade secret	10-20
an aliphatic diamine	trade secret	4-10
dipropylene glycol monomethyl ether	34590-94-8	15-25

### SECTION 3 PRECAUTIONARY LABEL INFORMATION

CAUTION: COMBUSTIBLE MIXTURE. HARMFUL OR FATAL IF SWALLOWED. Contains amines with a petroleum distillate as carrier. If swallowed do not induce vomiting, but rather drink milk or water and see a doctor at once. Wash off of skin with soap and water. Flush from eyes with water for at least 15 minutes. If skin or eye irritation persists, see a doctor. KEEP AWAY FROM SMALL CHILDREN.

### SECTION 4 FIRST AID INFORMATION

EYES: Immediately flush for at least 15 minutes while holding eyelids open. If irritation persists call a doctor.

SKIN: Immediately wash with soap and water. For a large splash, flood body under a shower with soap and warm water. If skin irritation that follows is severe or persistent see a doctor.

INGESTION: Do not induce vomiting. Give water or milk. see a doctor at once.

INHALATION: Remove to fresh air. Treat symptoms. If discomfort persists see a doctor.

NOTE TO PHYSICIAN: Based on the individual reactions of the patient, the physician's judgement should be used to control symptoms and clinical condition. Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be needed.

CAUTION: If unconscious, having trouble breathing or in convulsions, do not induce vomiting or give water.



## MATERIAL SAFETY DATA SHEET

PRODUCT

**FUEL RIGHT<sup>®</sup> 6000**  
(Bulk Fuel Additive)

Last Revised 1/17/2008

*Emergency Telephone Number:* CHEMTREC (800) 424-9300

### SECTION 5 HEALTH EFFECTS INFORMATION

PRIMARY ROUTE(S) OF EXPOSURE: Eye, Skin, and Inhalation

EYE CONTACT: Corrosive to the eyes with possible permanent damage depending on the length of exposure and on the first aid action taken.

SKIN CONTACT: Severely irritating to the skin if not removed promptly.

INGESTION: Can be harmful.

INHALATION: Inhalation of vapor may be harmful.

SYMPTOMS OF EXPOSURE: A review of available data does not identify any symptoms from exposure not previously mentioned.

AGGRAVATION OF EXISTING CONDITIONS: A review of available data does not identify any worsening of existing conditions

### SECTION 6 TOXICOLOGY INFORMATION

TOXICOLOGY STUDIES: Toxicology studies have not been conducted on this product, but a review of available data on the ingredients indicates that the product is not likely to be either a mutagen or a teratogen.

### SECTION 7 PHYSICAL AND CHEMICAL PROPERTIES

COLOR: Pale yellow or amber

FORM: Liquid

ODOR: Hydrocarbon/Fish Oil/Ammonia

DENSITY: 7.5-7.6 lbs./gal

PERCENT VOLATILE: N.D.

SPECIFIC GRAVITY: 0.90-0.91 @ 68° F

SOLUBILITY IN WATER: Partially soluble.

VISCOSITY: 3.0-4.0 cst @ 77° F [ASTM D445]

POUR POINT: Less than 0° F

FLASH POINT: 150° F

NOTE: These physical properties are typical values for this product.

### SECTION 8 FIRE AND EXPLOSION INFORMATION

FLASH POINT: 149 Degrees F minimum, 150° F typical

FLAMMABLE LIMITS: LEL: 1.8 UEL: 11.7 @ 77° F (estimate – based on most flammable ingredient)

AUTOIGNITION TEMPERATURE: 830° F (estimate – based on most flammable ingredient)

EXTINGUISHING MEDIA: Based on the NFPA guide, use dry chemical, foam, carbon dioxide or other extinguishing agent suitable for Class B fires. Use water to cool containers exposed to fire. For large fires, use water spray or fog, thoroughly drenching the burning material.

UNUSUAL FIRE AND EXPLOSION HAZARD: Containers exposed in a fire should be cooled with water to prevent vapor pressure buildup leading to a rupture.



## MATERIAL SAFETY DATA SHEET

PRODUCT

**FUEL RIGHT<sup>®</sup> 6000**  
(Bulk Fuel Additive)

Last Revised 1/17/2008

*Emergency Telephone Number:* CHEMTREC (800) 424-9300

### SECTION 9 REACTIVITY INFORMATION

INCOMPATIBILITY: Contact with strong oxidizers can generate heat, fires, explosions and toxic fumes.

THERMAL DECOMPOSITION: When burned, CO, CO<sub>2</sub> and NO<sub>x</sub> may be formed. Do not breathe smoke or fumes. Wear suitable protective equipment.

### SECTION 10 PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: If it is possible to generate significant vapors or mists, a NIOSH approved respirator is recommended.

For large spills, entry into large tanks, vessels or enclosed small spaces with inadequate ventilation, a pressure-demand, self-contained breathing apparatus is recommended.

VENTILATION: General ventilation is recommended. Additionally, local exhaust ventilation is recommended where vapors or mists may be released.

PROTECTIVE EQUIPMENT: When handling large quantities of this product, wear a full face shield and/or chemical splash goggles, impermeable gloves, and a plastic or rubber apron. Examples of impermeable gloves available on the market are neoprene and nitrile rubber. A full slicker suit is recommended if gross exposure is likely.

The availability of an eye wash fountain and safety shower is recommended.

If clothing becomes contaminated, remove clothing and thoroughly wash the affected area. Launder contaminated clothing before reuse.

### SECTION 11 SPILL AND DISPOSAL INFORMATION

IN CASE OF TRANSPORTATION ACCIDENTS, CALL CHEMTREC AT (800) 424-9300.

SPILL CONTROL AND RECOVERY: For small liquid spills, contain with absorbant material such as paper towels or oil-absorbant granules. Dispose of in an approved landfill or incinerator.

For large liquid spills, dike to prevent further movement and reclaim into recovery or salvage drums or tank truck for disposal. Refer to CERCLA in Section 14.

DISPOSAL: If this product becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261, since it does not have the characteristics of Subpart C, nor is it listed under Subpart D. Can be incinerated in accordance with local, state and federal regulations.

METAL OR PLASTIC CONTAINERS: Triple rinse (or equivalent) with a detergent/water solution – preferably hot. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities. If burned, stay out of the smoke.



## MATERIAL SAFETY DATA SHEET

PRODUCT

**FUEL RIGHT<sup>®</sup> 6000**  
(Bulk Fuel Additive)

Last Revised 1/17/2008

*Emergency Telephone Number:* CHEMTREC (800) 424-9300

### **SECTION 12 ENVIRONMENTAL INFORMATION**

**ENVIRONMENTAL HAZARDS:** This product is toxic to fish. Do not discharge into lakes, streams, ponds or public waters. Do not contaminate water by cleaning of equipment or disposal of wastes.

**AQUATIC TOXICITY RATING:** This product has not been rated as to degree of toxicity, but ingredients listed in Section 2 are known to be rated TOXIC with LC50 as low as 1 ppm determined with various species of fish and *Daphnia magna*.

### **SECTION 13 TRANSPORTATION INFORMATION**

**PROPER SHIPPING NAME/HAZARD CODE:** Regulated only when shipped in containers exceeding 119 US gallons capacity.

COMBUSTIBLE LIQUID n.o.s.

CONTAINS HEAVY AROMATIC NAPHTHA & DPM GLYCOL ETHER

CLASS: COMBUSTIBLE LIQUID, NA1993, PG III

NMFC NO. 155150 – FUEL ADDITIVE, COMBUSTIBLE (In non-bulk containers)

NMFC NO. 155250-10 – FUEL ADDITIVE, COMBUSTIBLE (In bulk containers more than 119 gallons each)

### **SECTION 14 REGULATORY INFORMATION**

The following regulations apply to this product:

FEDERAL REGULATIONS:

OSHA'S HAZARD COMMUNICATION RULE, 29 CFR 1910.1200:

Based on our hazard evaluation, the ingredients in this product are hazardous for the following reasons:

heavy aromatic naphtha – irritant, combustible  
dipropylene glycol monmethyl ether – combustible  
cyclic amino compound and aliphatic diamine – severe eye and skin irritants

CERCLA/SUPERFUND, 40 CFR 117, 302:

Notification of spills of this product is not required.

SARA/SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (TITLE III):

SECTION 302 – EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355):

This product does not contain ingredients listed in Appendix A and B as an Extremely Hazardous Substance.

SECTIONS 311 AND 312 – MATERIAL SAFETY DATA SHEET REQUIREMENTS (40 CFR 370):

Our hazard evaluation has found this product to be hazardous. The product should be reported under the following EPA hazard categories:

XX Immediate (acute) health hazard	-- Sudden release of pressure hazard
-- Delayed (chronic) health hazard	-- Reactive hazard
XX Fire hazard	



## MATERIAL SAFETY DATA SHEET

PRODUCT

**FUEL RIGHT<sup>®</sup> 6000**  
(Bulk Fuel Additive)

Last Revised 1/17/2008

*Emergency Telephone Number:* CHEMTREC (800) 424-9300

### **SECTION 14 REGULATORY INFORMATION (CONTINUED)**

SECTION 313 – LIST OF TOXIC CHEMICALS (40 CFR 372):

This product does not contain ingredients on the List of Toxic Chemicals.

TOXIC SUBSTANCES CONTROL ACT (TSCA):

The chemical ingredients in this product are on the 8(b) Inventory List (40 CFR 710).

RESOURCE CONSERVATION AND RECOVERY ACT (RCRA), 40 CFR 261 SUBPART C & D:

Consult Section 11 for RCRA classification.

FEDERAL WATER POLLUTION CONTROL ACT, CLEAN WATER ACT, 40 CFR 401.15 (formerly Sec. 307), 40 CFR 116 (formerly Sec. 311):

None of the ingredients in this product is specifically listed.

CLEAN AIR ACT, Sec. 111 (40 CFR 60), Sec. 112 (40 CFR 61, 1990 Amendments), Sec. 611 (40 CFR 82, CLASS I and II Ozone Depleting Substances):

This product does not contain ingredients covered by the Clean Air Act.

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65:

This product does not contain any chemicals which require warning under California Proposition 65.

MICHIGAN CRITICAL MATERIALS:

This product does not contain ingredients listed on the Michigan Critical Materials Register.

INTERNATIONAL REGULATIONS:

This product is exempt from WHMIS under the House of Commons of Canada Bill C-70.

### **SECTION 15 ADDITIONAL INFORMATION**

None.

### **SECTION 16 USER'S RESPONSIBILITY**

This product material safety data sheet provides health and safety information. The product is to be used in applications consistent with our product literature. Individuals handling this product should be informed of the recommended safety precautions and should have access to this information. For any other uses, exposures should be evaluated so that appropriate handling practices and training programs can be established to ensure safe workplace operation. Please call the phone numbers listed BELOW for any further information.

PREPARED BY: Robert E. Tatnall, President, Fairville Products, Inc.